


# COEX™ C2000 TriMode Series '3' Camera Station

The COEX™ C2000 TriMode camera station 3 series has been specifically developed for marine applications and demanding environments. Combining the latest thermal imaging technology with a day / night (color / mono) camera module the C2000 TriMode camera stations ensure unprecedented visual feedback in all light conditions.



Utilized around the world to assist with:

- Navigation during night time and foggy conditions
- Ice Detection
- Piracy Detection
- Man-overboard Safety
- Environmental Protection
- Intruder Detection
- Safety and Security Protection

Even during daylight the C2000 TriMode can provide increased visibility over conventional camera stations with human detection at over 1100 m<sup>\*3/4</sup>

COEX Series 3 camera stations are fitted with a 384 x 288 analogue thermal imaging camera and a high resolution analogue day / night camera with removable IR cut filter.

## Features

- IP66 & IP67 rated – completely protected against dust & water ingress, for the most extreme environments
- Electro-polished 316L stainless steel, for maximum corrosion resistance
- TriMode Operation – Day (color), Night (mono) and Thermal Imaging
- Low Voltage Operation
- Preset accuracy and repeatability of <0.05°
- Advanced Mechanical Design to minimize size and weight
- Pre-Heat Mode for safe start up in freezing conditions
- Smart Move Technology assists target acquisition and tracking
- Germanium and Toughened Glass Windows

## Options

- Continuous Rotation [C]
- Absolute Positioning
- Integral Wiper [W]
- COEX™ “MEWS” Pressurized Wash System
- Synectics IP and Fiber Optic Transmission (via associated junction box)
- COEX™ Wall Mount Bracket
- COEX™ Range of Tilt Down Towers and accessories

# Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]
Certifications / Ratings	IP66 & IP67 to IEC 60529 CE Compliant to EMC and Low Voltage Directives LVD Directive: 2006/95/EC	
ENVIRONMENTAL		
Operating Temperature	-45°C to +60°C	
MECHANICAL		
Material	Electro-polished 316L Stainless Steel	
Windows	Germanium and Toughened Glass, Thermostatically Operated Demister [Wiper for Day / Night View only]	
Pan Operation	360° rotation @ 0° to 42° /sec; Mechanical limits; Programmable soft-stops; Preset Positioning [Continuous Rotation]	
Tilt Operation	180° rotation @ 0° to 21° / sec; Mechanical Limits; Programmable Soft-stops; Preset Positioning	
Mounting	4 x M8 x 1.25 tapped holes, equi-spaced on a 4" (101.6 mm) P.C.D.	
Dimensions (W x D x H)	412 x 310 x 375 mm	
Pan Turning Circle	Ø 626 mm	
Weight*1	19 kg	
ELECTRICAL		
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)	
Power Consumption	92VA Maximum	
TELEMETRY		
Interface	RS485 serial asynchronous data	
Protocols	Synectics™, Pelco®, and other industry standard protocols available	
Functions*1	Pan, Tilt, Wash*2, Wipe*2 Aux1, [Aux2] and Aux in	
Day / Night Camera	On / Off Selection of: Digital Zoom, BLC, Autofocus	
Functions*2	Auto / Manual Selection of: Focus, Color / Mono Operation, Frame Integration, White Balance	
Thermal Camera	Continuous Electronic Zoom, Multiple Color Palettes (including Inverted), Multiple Contrast Display,	
Functions*1	Contrast and Level Control, Hot and Cold Spot, Auto / Manual Shuttering	
OSD	Password protected on-screen menu system for camera station configuration and diagnostics	
CAMERA / LENS		[OPTIONS]
	<b>C2000-2V36-T3&gt;&gt; [2C36] [W]*5</b>	<b>C2000-2V10-T3&gt;&gt; [2C10] [W]*5</b>
Video Output	1.0 Vpk-pk CVBS into 75Ω; Color PAL 50Hz [NTSC 60Hz]	
Image Sensor	¼" EXview HAD CCD	⅓" Super HAD CCD II
Resolution	>550TVL	>530TVL
S/N Ratio	>50dB	
Zoom Range	36x zoom (up to 432x with digital zoom)	10x zoom (up to 120x with digital zoom)
Minimum Illumination	1.4 lux 0.1 lux (with ⅓ sec integration) 0.01 lux mono (with ⅓ sec integration)	0.25 lux 0.015 lux (with ⅓ sec integration) 0.0004 lux mono (with ⅓ sec integration)
Focal Length	3.4 to 122.4 mm	5.1 to 51 mm
Angle of View	57.8° to 1.7°	52° to 5.4°
Aperture	F1.6 to 4.5	F1.8 to 2.1
THERMAL IMAGER		[OPTIONS]
	<b>C2000-2V&lt;&lt;-T345 [2C&lt;&lt;] [W]*5</b>	<b>C2000-2V&lt;&lt;-T315 [2C&lt;&lt;] [W]*5</b>
Image Sensor	Amorphous Silicon Microbolometer	
Spectral Response	8 – 14 μm	
Thermal Sensitivity	50mK	
Refresh Rate	<9Hz [25Hz]	
Resolution	384 x 288	
Fixed Focal Length	45 mm	15 mm
Angle of View	12° x 9.3°	35° x 26°
Human Detection*3/4	~1000 m	>200 m

NOTE: \*1 Dependant on equipment fitted. \*2 Refer to Synectics for availability and compatibility with other control systems \*3 Based on Johnson Criteria.  
\*4 Actual range may vary depending on camera set-up, user experience, environmental conditions and type of monitor or display used. \*5 >> replace with thermal camera module and << replace with day / night camera module.

## Synectic Systems

sales@synecticsglobal.com

synecticsglobal.com

Specifications subject to change. E & OE.

Copyright © Synectic Systems Group Ltd., Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2015. All Rights Reserved.

MANUFACTURER OF



CAMERA STATIONS

Reference Numbers: 03GF0583\_2  
C2000T2S3/0215/USL Iss 3