

COEX™ C2000-1V Marine Camera Station

The COEX™ C2000-1V camera station has a unique compact and lightweight design specifically developed for marine applications. The camera stations are designed for toughness and durability to operate in the most adverse environments – from extremely low temperatures where ice is prevalent to severe weather conditions on all types of vessels to the high temperatures experienced in deserts.



The COEX™ C2000 marine camera stations are manufactured from the highest grade, corrosion resistant, electro-polished 316L stainless steel – incorporating state of the art camera and control options.

The advanced mechanical design of a virtually indestructible gearbox combined with backlash eliminating technology ensures smooth and accurate camera control. Preset accuracy and repeatability of <math><0.05^\circ</math> provides a reliable solution for both security and process monitoring.

The COEX™ C2000 camera stations can operate in the most extreme environments from as low as

Features

- DNV Type Approval
- CSAus Certification
- CSA Canadian Certification
- EAC-TR CU
- IP66 & IP67 Rated – Completely Protected Against Dust & Water Ingress, for the Most Demanding Environments
- Type 6 Enclosure
- Electro-polished 316L Stainless Steel, for Maximum Corrosion Resistance
- Low Voltage Operation
- Pre-Heat Mode

- AC Stepper Motor Drive for Variable Speed Control with High Preset Accuracy and Repeatability
- Onscreen Menu Display Allowing Easy Configuration and Diagnostics
- Single Stationary Cable Tail
- Multi-protocol Telemetry for Extensive System Compatibility

Options

- Integral Wiper [W]
- COEX™ 'MEWS' Wash System
- IP, Fiber Optic Available with Associated Junction Box
- Continuous Rotation
- Thermal Imaging

Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]	
Certifications / Ratings	DNV Type Approval CSAus / CSA Canadian Class 3862 13 and Class 3862 93 EAC-TR CU EMC:61000 CE Compliant IP66 & IP67 to IEC 60529 Type 6 Enclosure		
ENVIRONMENTAL			
Operating Temperature*1	-45°C to +70°C		
MECHANICAL			
Material	Electro-polished 316L Stainless Steel		
Window	Toughened Glass, Thermostatically Operated Demister [Wiper]		
Pan Operation	360° Rotation; 0° to 42°/sec; Mechanical limits; programmable soft-stops; preset positioning [Continuous Rotation]		
Tilt Operation	180° Rotation; 0° to 21°/sec; Mechanical limits; programmable soft-stops; preset positioning		
Mounting	4 x M8 x 1.25 tapped holes, equi-spaced on a 4" (101.6 mm) P.C.D.		
Dimensions (W x D x H)	14.29" x 12.21" x 13.31"		
Pan Turning Circle	Ø 16.77"		
Weight	35 lbs		
ELECTRICAL			
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)		
Power Consumption	100VA Maximum		
TELEMETRY			
Interface	RS485 serial asynchronous data		
Protocols*2	Synectics™, Pelco®, and other industry standard protocols available		
Functions*1	Pan, Tilt, Zoom, Wipe, Wash, Aux1 [Aux2] and Aux In		
Day / Night Camera Functions*1	Optical Zoom, Digital Zoom, BLC, Autofocus, Focus, Color / Mono, Iris, Auto Iris, Frame Integration, White Balance		
OSD	Password protected on-screen menu system for camera station configuration and diagnostics		
CAMERA / LENS		C2000-1V36 [W]	C2000-1V10 [W]
Video Output	1.0 Vpk-pk CVBS into 75Ω Color NTSC 60Hz [PAL 50Hz]		
Image Sensor	¼" EXview HAD CCD	⅓" Super HAD CCD II	
Resolution	>550TVL	>530TVL	
S/N Ratio	>50dB		
Zoom Range	36x zoom (up to 432x with digital zoom)	10x zoom (up to 120x with digital zoom)	
Minimum Illumination	1.4 lux (1/60 integration) 0.1 lux (¼ integration) 0.01 lux (¼ integration)	0.25 lux (1/60 integration) 0.015 lux (¼ integration) 0.0004 lux (¼ integration)	
Focal Length	3.4 to 122.4 mm	5.1 to 51 mm	
Angle of View (H)	57.8° to 1.7°	52° to 5.4°	
Aperture	F1.6 to 4.5	F1.8 to 2.1	

NOTE: *1 Dependant on equipment fitted. *2 Refer to Synectics for availability and compatibility with other control systems.

Synectic Systems

sales@synecticsglobal.com

synecticsglobal.com

Specifications subject to change. E & OE.

Copyright © Synectic Systems Group Ltd., Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2015. All Rights Reserved.

MANUFACTURER OF



CAMERA STATIONS

Reference Numbers: 03GF0509_1
C2000-1V/0215/USL Iss 9