

COEX™ C3000-1V Ex d Camera Station

The COEX™ C3000-1V camera series has a unique compact and lightweight design specifically developed for hazardous area applications. The camera stations are designed for toughness and durability to operate in the most adverse environments – from offshore oil and natural gas rigs to FPSO / FSO's and LPG / LNG tanker vessels



The COEX™ C3000 Ex d camera stations are manufactured from high grade, corrosion resistant, electro-polished 316 stainless steel – incorporating state of the art cameras, control and transmission modules.

The advanced mechanical design of a virtually indestructible gearbox combined with backlash eliminating technology ensures smooth proportional speed control at fast and slow speeds. Preset accuracy and repeatability of <math><0.05^\circ</math> provides a reliable solution for both security and process monitoring.

The COEX™ C3000 camera stations can operate in the most extreme environments and are certified for temperatures as low as

Features

- ATEX Certification
- CSAus Certification
- IECEx Certification
- CSA Canadian Certification
- EAC-TR CU Certification
- DNV Type Approval
- IP66 & IP68 Rated – Completely Protected Against Dust & Water Ingress, for the Most Demanding Environment
- Type 6 Enclosure
- C-Tick Compliance
- Electro-polished 316 Stainless Steel, for Optimum Corrosion Resistance
- Low Voltage Operation
- Pre-Heat Mode
- AC Stepper Motor Drive for Variable Speed Control with High Preset Accuracy and Repeatability
- Onscreen Menu Display Allowing Easy Configuration and Diagnostics
- Single Stationary Cable Tail
- Multi-protocol Telemetry for Extensive System Compatibility

Options

- Integrated IP Encoder
- Integral Wiper [W]
- COEX™ 'FEWS' Ex Pressurized Wash System
- Integral Fiber Optic Transmission with Alternative Base
- Continuous Rotation
- Thermal Imaging

Specifications

CERTIFICATIONS / RATINGS		[OPTIONS]
Certifications / Ratings	ATEX / IECEx: ATEX II 2GD, Ex d IIC Gb; Ex tb IIIC Db; T4 / T5 / T6 US Class / Division: Class I, Div 1, Groups A, B, C, D; Class II, Div I, Groups E, F, G; T4 / T5 / T6 US Class / Zone: Class I, Zone 1, AEx d IIC Gb; Zone 21, AEx tb IIIC Db; T4 / T5 / T6 CAN: Ex d IIC Gb; Ex tb IIIC Db; Class II, Div 1, Groups E, F, G, Class III, Div 1; T4 / T5 / T6 EAC-TR CU Certification DNV Type Approval EMC:61000 CE Compliant IP66 & IP68 (30m Submersion for 4 hrs) to IEC 60529 Type 6 Enclosure C-Tick Compliant	
ENVIRONMENTAL		
Rated Temperature	-67°F (-55°C) to 140°F (+60°C) [158°F / +70°C]	
MECHANICAL		
Material	Electro-polished 316 Stainless Steel	
Window	Toughened Glass, Thermostatically Operated Demister [Wiper]	
Pan Operation	360° Rotation; 0° to 42°/sec; Mechanical limits; programmable soft-stops; preset positioning [Continuous Rotation]	
Tilt Operation	180° Rotation; 0° to 21°/sec; Mechanical limits; programmable soft-stops; preset positioning	
Mounting	4 x M8 tapped holes, equispaced on a 4" (101.6 mm) P.C.D.	
Dimensions (W x D x H)	14.76" x 12.20" x 13.86" [Alternative Base 14.76" x 12.20" x 14.29"]	
Pan Turning Circle	Ø 22.05"	
Weight*1	55 lbs [Alternative Base 59.5 lbs]	
ELECTRICAL		
Power Requirements	24Vac 50 / 60Hz or 24Vdc (±10%)	
Power Consumption	75VA Maximum	
TELEMETRY		
Interface	RS485 serial asynchronous data	
Protocols*2	Synectics™, Pelco®, and other industry standard protocols available	
Functions*1	Pan, Tilt, Zoom, Focus, Wipe, Wash, Aux1, [Aux2] and Aux In	
Day / Night Camera Functions*1	Optical Zoom, Digital Zoom, BLC, Autofocus, Focus, Color / Mono, Iris, Auto Iris, Frame Integration, White Balance	
OSD	Password protected on-screen menu system for camera station configuration and diagnostics	
CAMERA / LENS		
	C3000-1V36 [W]	C3000-1V10 [W]
Video Output	1.0 Vpk-pk CVBS into 75Ω Color NTSC 60Hz [PAL 50Hz]	
Image Sensor	¼" EXview HAD CCD	½" Super HAD CCD II
Resolution	>550TVL	>530TVL
S/N Ratio	>50dB	
Zoom Range	36x zoom (up to 432x with digital zoom)	10x zoom (up to 120x with digital zoom)
Minimum Illumination	1.4 lux	0.25 lux
	0.1 lux (with ½ sec integration)	0.015 lux (with ½ sec integration)
	0.01 lux mono (with ½ sec integration)	0.0004 lux mono (with ½ sec integration)
Focal Length	3.4 to 122.4 mm	5.1 to 51 mm
Angle of View (H)	57.8° to 1.7°	52° to 5.4°
Aperture	F1.6 to 4.5	F1.8 to 2.1

NOTE: *1 Dependant on equipment fitted. *2 Refer to Synectics for availability and compatibility with other control systems.

Synectic Systems

sales@synecticsglobal.com

synecticsglobal.com

Specifications subject to change. E & OE.

Copyright © Synectic Systems Group Limited, Synectic Systems, Inc., Synectic Systems (Asia) Pte. Limited 2015. All Rights Reserved.

MANUFACTURER OF



CAMERA STATIONS

Reference Number:
C3000-1V/0615/USL Iss 8